






**8156**
**brache per sollevamento 3t giallo nastro piatto a due strati, asole rinforzate, poliestere alta tenacità (PES)**

CE

UNI EN 1492-1



art.	art.	L m		
081560010	8156 1-T3	1	90	3
081560015	8156 1,5-T3	1,5	90	3
081560020	8156 2-T3	2	90	3
081560025	8156 2,5-T3	2,5	90	3
081560030	8156 3-T3	3	90	3
081560035	8156 3,5-T3	3,5	90	3
081560040	8156 4-T3	4	90	3
081560050	8156 5-T3	5	90	3
081560060	8156 6-T3	6	90	3
081560080	8156 8-T3	8	90	3
081560100	8156 10-T3	10	90	3
081560120	8156 12-T3	12	90	3

				$\beta=0^{\circ}+45^{\circ}$ 	$\beta=45^{\circ}+60^{\circ}$ 
30	1t	0,8t	2t	1,4t	1t
60	2t	1,6t	4t	2,8t	2t
90	3t	2,4t	6t	4,2t	3t
120	4t	3,2t	8t	5,6t	4t
150	5t	4,0t	10t	7,0t	5t
180	6t	4,8t	12t	8,4t	6t
240	8t	6,4t	16t	11,2t	8t
300	10t	8,0t	20t	14,0t	10t